



Split Ceramic Eyelets (Flange on one side, split on side for ease of threading)

PLEASE NOTE: Measurements may vary slightly due to ceramic shrinkage during the firing process.

PART #	A		B		C		D		E		F		G	
	Inch	MM	Inch	MM	Inch	MM	Inch	MM	Inch	MM	Inch	MM	Inch	MM
C-015-AP	0.138	3.5	0.209	5.3	0.079	2.0	0.118	3.0	0.150	3.8	0.105	2.7	0.028	0.7
C-015-T	0.138	3.5	0.209	5.3	0.079	2.0	0.118	3.0	0.168	4.3	0.105	2.7	0.032	0.8
C-010-AP	0.146	3.7	0.209	5.3	0.071	1.8	0.118	3.0	0.165	4.2	0.079	2.0	0.040	1.0
C-095-AP	0.150	3.8	0.203	5.2	0.084	2.1	0.079	2.0	0.118	3.0	0.105	2.6	0.040	1.0
C-097-AP	0.210	5.4	0.276	7.0	0.142	3.6	0.074	1.9	0.121	3.1	0.107	2.6	0.107	2.6
C-101-AP	0.259	6.6	0.311	7.9	0.110	2.8	0.251	6.4	0.229	7.6	0.094	2.4	0.094	2.4
C-050-AP	0.273	6.9	0.358	9.1	0.075	1.9	0.131	3.3	0.191	4.9	0.230	5.8	0.066	1.7
C-067-AR	0.295	7.5	0.394	10.0	0.197	5.0	0.118	3.0	0.197	5.0	0.125	3.2	0.079	2.0
C-083-AP	0.315	8.0	0.433	11.0	0.118	3.0	0.079	2.0	0.138	3.5	0.118	3.0	0.118	3.0
C-012-TC	0.315	8.0	0.409	10.4	0.125	3.2	0.138	3.5	0.217	5.5	0.169	4.3	0.055	1.4
C-100-AP	0.381	9.7	0.492	12.5	0.216	5.5	0.279	7.1	0.385	9.8	0.165	4.2	0.165	4.2